



**SPECIFICATIONS**

**ELECTRICAL**

- Contact Current Rating : 1.5 Amperes
- Contact Resistance : 30 mΩ Max
- Insulator Resistance : 1000MΩ Min
- Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds
- Operating Voltage : 150V AC Max

**MATERIAL**

- Insulator : PBT UL94V-0
  - Contact : Phosphor Bronze
  - Contact Plated : Gold Plated + Tin Plated + Selective Plated
  - Shield : Nickel Plated Brass Alloy
- MECHANICAL**
- Insertion Force : 35Newtons Max
  - Extraction Force : 10Newtons Min
  - Durability (life test) : 1500 cycles

UNIT : mm

**MORLINKOM TECHNOLOGY LTD.**

**CENTRONIC PRECISION ELECTRONIC COMPANY** MORLINKOM TECHNOLOGY LTD  
 三川精密電子有限公司 魔林科技有限公司  
 TEL: 886-2-2686-8788 FAX: 886-2-2686-0018  
 E-MAIL: Centron@tp6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖	DRAWN BY	日期	DATE
核對	FUFU	2009/09/04	
CHECKED BY	WENDY	比例	SCALE
		1:1	

**USB-BS-W**  
 圖號 930-BS-W  
 DRAWING NO.