



**SPECIFICATIONS**

**ELECTRICAL**

- Contact Current Rating : 1.5 Amperes
- Contact Resistance : 30 mΩ Max
- Insulator Resistance : 1000MΩ Min
- Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds
- Operating Voltage : 150V AC Max

**MATERIAL**

- Insulator : PBT UL94V-0
- Contact : Phosphor Bronze
- Contact Plated : Gold Plated , Tin Plated , Selective Plated
- Shield : Nickel Plated Brass Alloy

**MECHANICAL**

- Insertion Force : 35Newtons Max
- Extraction Force : 10Newtons Min
- Durability(life test) : 1500 cycles

UNIT : mm

MORLINKOM TECHNOLOGY LTD.

CENTRONIC PRECISION ELECTRONIC COMPANY  
 三川精密電子有限公司  
 TEL:886-2-2686-8788 FAX:886-2-2686-0018  
 E-MAIL: Centron@tpts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD  
 魔林科技有限公司  
 TEL:886-2-2686-8788 FAX:886-2-2686-0018  
 E-MAIL: Cen88888@gmail.com

|            |          |            |       |
|------------|----------|------------|-------|
| 繪圖         | DRAWN BY | 日期         | DATE  |
| 核對         | FUFU     | 2009/04/20 |       |
| CHECKED BY | WENDY    | 比例         | SCALE |
|            |          | 1:1        |       |

**USB-2AR-W/B**

圖號 930-2AR-W/B  
 DRAWING NO.