



## SPECIFICATIONS

### ELECTRICAL

- Contact Current Rating : 1.5 Amperes
- Contact Resistance : 30 m $\Omega$  Max
- Insulator Resistance : 1000M $\Omega$  Min
- Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds
- Operating Voltage : 150V AC Max

### MATERIAL

- Insulator : PBT UL94V-0
- Contact : Phosphor Bronze
- Contact Plated : Gold Plated , Tin Plated , Selective Plated
- Shield : Nickel Plated Brass Alloy

### MECHANICAL

- Insertion Force : 35Newtons Max
- Extraction Force : 10Newtons Min
- Durability(Life test) : 1500 cycles

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY

三川精密電子有限公司

TEL:886-2-2686-8788

E-MAIL: Centron@tpsts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD

魔林科技有限公司

FAX:886-2-2686-0018

E-MAIL: Cen88888@gmail.com

繪圖 DRAWN BY

FUFU

日期 DATE

2008/12/30

USB-AR-W/B

圖號

930-AR/B

核對 CHECKED BY

WENDY

比例 SCALE

1:1

DRAWING NO.

DRAWING NO.

MORLINKOM TECHNOLOGY LTD.