



SPECIFICATIONS

- Voltage rating : 50V AC/DC
- Current Rating : 0.5A AC/DC
- Withstanding Voltage : 250V AC/minute
- Insulator Resistance : 100MΩ Min
- Temperature Range : -25°C ~ +85°C
- Contact Resistance : 30MΩ Max
- Material : Pin : Phosphor Bronze/Tin-Plated

Solder Tabs : Phosphor Bronze/Tin-Plated

Housing : Nylon 6T UL94V-0

Cover : Nylon 46, UL94V-0

CONTACTS	DIMENSIONS			CONTACTS	DIMENSIONS		
	A	B	C		A	B	C
6	2.50	7.40	3.60	26	12.50	17.40	13.60
7	3.00	7.90	4.10	27	13.00	17.90	14.10
8	3.50	8.40	4.60	28	13.50	18.40	14.60
9	4.00	8.90	5.10	29	14.00	18.90	15.10
10	4.50	9.40	5.60	30	14.50	19.40	15.60
11	5.00	9.90	6.10	31	15.00	19.90	16.10
12	5.50	10.40	6.60	32	15.50	20.40	16.60
13	6.00	10.90	7.10	33	16.00	20.90	17.10
14	6.50	11.40	7.60	34	16.50	21.40	17.60
15	7.00	11.90	8.10	35	17.00	21.90	18.10
16	7.50	12.40	8.60	36	17.50	22.40	18.60
17	8.00	12.90	9.10	37	18.00	22.90	19.10
18	8.50	13.40	9.60	38	18.50	23.40	19.60
19	9.00	13.90	10.10	39	19.00	23.90	20.10
20	9.50	14.40	10.60	40	19.50	24.40	20.60
21	10.00	14.90	11.10	45	22.00	26.90	23.10
22	10.50	15.40	11.60	50	24.50	29.40	25.60
23	11.00	15.90	12.10	55	27.00	31.90	28.10
24	11.50	16.40	12.60	60	29.50	34.40	30.60
25	12.00	16.90	13.10				

UNITS: MM

CENTRONIC PRECISION ELECTRONIC COMPANY

三川精密電子有限公司

TEL: 886-2-2686-8788

FAX: 866-2-2686-0018

E-MAIL: Centron@ppts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD

魔林科技有限公司

FAX: 866-2-2686-0018

E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY

FUFU

核對 CHECKED BY

WENDY

日期 DATE

2011/03/09

比例 SCALE

1:1

0.5FPCRXXTBASP

圖號 768-XXR-SDP-A

DRAWING NO.