



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 0.5 Ampere
- Contact Resistance : 20 mΩ Max
- Insulator Resistance : 500 MΩ Min
- Dielectric Withstanding Voltage : 200 V AC RMS 60 Seconds
- Voltage Rating : 50 V

MATERIAL

- Insulator : LCP6807 , Cover : LCP6130
- Contact : Phosphor Bronze
- Plated : Gold Plated , Tin Plated , Selective Plated
- Operation Temperature : - 25°C to + 85°C

CONTACTS		DIMENSIONS				CONTACTS		DIMENSIONS			
A	B	C	D	A	B	C	D	A	B	C	D
4	3.00	5.05	9.20	11.00	20	19.00	21.05	25.20	27.00		
5	4.00	6.05	10.20	12.00	21	20.00	22.05	26.20	28.00		
6	5.00	7.05	11.20	13.00	22	21.00	23.05	27.20	29.00		
7	6.00	8.05	12.20	14.00	23	22.00	24.05	28.20	30.00		
8	7.00	9.05	13.20	15.00	24	23.00	25.05	29.20	31.00		
9	8.00	10.05	14.20	16.00	25	24.00	26.05	30.20	32.00		
10	9.00	11.05	15.20	17.00	26	25.00	27.05	31.20	33.00		
11	10.00	12.05	16.20	18.00	27	26.00	28.05	32.20	34.00		
12	11.00	13.05	17.20	19.00	28	27.00	29.05	33.20	35.00		
13	12.00	14.05	18.20	20.00	29	28.00	30.05	34.20	36.00		
14	13.00	15.05	19.20	21.00	30	29.00	31.05	35.20	37.00		
15	14.00	16.05	20.20	22.00	31	30.00	32.05	36.20	38.00		
16	15.00	17.05	21.20	23.00	32	31.00	33.05	37.20	39.00		
17	16.00	18.05	22.20	24.00	33	32.00	34.05	38.20	40.00		
18	17.00	19.05	23.20	25.00	34	33.00	35.05	39.20	41.00		
19	18.00	20.05	24.20	26.00							

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD
 三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL: Centron@pts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY FUJFU
 核對 CHECKED BY WENDY

日期 DATE 2011/03/09
 比例 SCALE 1:1

1.0FPC5X7BAS

圖號 DRAWING NO. 763-XX-S