



**SPECIFICATIONS**

**ELECTRICAL**

- Contact Current Rating : 3 Amperes
  - Contact Resistance : 20 mΩ Max
  - Insulator Resistance : 5000 MΩ Min
  - Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds
- MATERIAL**
- Insulator : Nylon-6T , UL 94-0
  - Contact : Brass
  - Contact Plated : Gold Plated , Tin Plated , Selective Plated
  - Operation Temperature : - 40°C to + 105°C

A = mm

B = mm

C = mm

UNIT : mm

**CENTRONIC PRECISION ELECTRONIC COMPANY**

三川精密電子有限公司

TEL: 886-2-2686-8788 FAX: 886-2-2686-0018

E-MAIL: Centron@tpts6.seed.net.tw E-MAIL: Cen8888@gmail.com

**MORLINKOM TECHNOLOGY LTD**

魔林科技有限公司

E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY FU FU	日期 DATE 2009/02/06
核對 CHECKED BY WENDY	比例 SCALE 1:1

**SPHS1XXGB1XX**

圖號 105-XX-XX  
DRAWING NO.

**TECHNOLOGY LTD.**