



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 3 Amperes
- Contact Resistance : 4 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Operating Voltage : 60V AC/DC

MECHANICAL

- Insertion Force : 250 g / Pin Max
- Extraction Force : 50 g / Pin Min
- Mechanical Life Cycle : 200 Min

MATERIAL

- Insulator : PPS , UL 94V-0
- Contact : Beryllium Copper (BeCu)
- Contact Plated : Selective Gold Plated Over Nickel
- Pin(Outer Sleeve) : Brass , Tin Plated 、 Gold plated

Operation Temperature : Gold Plated : - 55°C to + 125°C
 Tin Plated : - 40°C to + 105°C

UNIT: mm

MORINKOM TECHNOLOGY LTD

CENTRONIC PRECISION ELECTRONIC COMPANY MORINKOM TECHNOLOGY LTD
 三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL:Centron@tpst6.secd.net.tw E-MAIL:Cent8888@gmail.com

繪圖	DRAWN BY
核對	CHECKED BY
FUFU	WENDY

日期	DATE
比例	SCALE
2009/12/23	1:1

PR2XYSB1P7

圖號 150-XX-P7
 DRAWING NO.