



## SPECIFICATIONS

### ELECTRICAL

- Contact Current Rating : 3 Amperes
- Contact Resistance : 4 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Operating Voltage : 60V AC/DC

### MECHANICAL

- Insertion Force : 50 g / Pin
- Extraction Force : 15 g / Pin
- Mechanical Life Cycle : 200 Min

### MATERIAL

- Insulator : PPS , UL 94V-0
- Contact : Beryllium Copper ( BeCu )
- Contact Plated : Selective Gold Plated Over Nickel
- Pin(Outer Sleeve) : Brass , Tin Plated 、 Gold plated

**Operation Temperature** : Gold Plated : - 55°C to + 105°C  
 Tin Plated : - 40°C to + 105°C

UNIT: mm

CENTRONIC PRECISION ELECTRONIC COMPANY  
 三川精密電子有限公司  
 TEL:886-2-2686-8788 FAX:886-2-2686-0018  
 E-MAIL:Centron@tpst6.secd.net.tw

MORLINKOM TECHNOLOGY LTD  
 鹿林科技有限公司  
 E-MAIL: Cen8888@gmail.com

繪圖	DRAWN BY	日期	DATE
核對	CHECKED BY	比例	SCALE
	FUFU	2010/04/23	1:1
	WENDY		

HPR1XXSB1

圖號 142-XX  
 DRAWING NO.