



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 3 Amperes
- Contact Resistance : 4 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Operating Voltage : 60V AC/DC

MECHANICAL

- Insertion Force : 250 g / Pin
- Extraction Force : 50 g / Pin
- Mechanical Life Cycle : 200 Min

MATERIAL

- Insulator : PPS, UL 94V-0
- Contact : Beryllium Copper (BeCu)
- Contact Plated : Selective Gold Plated Over Nickel
- Pin(Outer Sleeve) : Brass, Tin Plated、Gold plated

Operation Temperature : Gold Plated : - 55°C to + 125°C

Tin Plated : - 40°C to + 105°C

- L = 6.6
- L = 9.52
- L = 13.08
- L = 16

UNIT: mm

MORINKOM TECHNOLOGY LTD.

CENTRONIC PRECISION ELECTRONIC COMPANY
 三川精密電子有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL:Centron@tpstsf.secd.net.tw

MORINKOM TECHNOLOGY LTD
 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL:Cent8888@gmail.com

繪圖	DRAWN BY	日期	DATE
核對	CHECKED BY	比例	SCALE
	FUFU	2009/05/18	1:1
	WENDY		

PRIXXSBILXX

圖號 140-XX-LXX
 DRAWING NO.