



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 3 Amperes
- Contact Resistance : 4 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Operating Voltage : 60V AC/DC

MECHANICAL

- Insertion Force : 250 g / Pin
- Extraction Force : 50 g / Pin
- Mechanical Life Cycle : 200 Min

MATERIAL

- Insulator : PPS , UL 94V-0
- Contact : Beryllium Copper (BeCu)
- Contact Plated : Selective Gold Plated Over Nickel
- Pin(Outer Sleeve) : Brass , Tin Plated 、 Gold plated

Operation Temperature : Gold Plated : - 55°C to + 125°C
 Tin Plated : - 40°C to + 105°C

UNIT: mm

CENTRONIC PRECISION ELECTRONIC COMPANY
 三川精密電子有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL:Centron@cpnts6.seed.net.tw E-MAIL:Cent8888@gmail.com

繪圖	DRAWN BY	日期	DATE
核對	CHECKED BY	比例	SCALE
	FUFU	2009/07/02	1:1
	WENDY		

PR2XXSB1

圖號 150-XX
 DRAWING NO.