



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 1.5 Amperes
- Contact Resistance : 30 mΩ Max
- Insulator Resistance : 1000MΩ Min
- Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds
- Operating Voltage : 150V AC Max

MATERIAL

- Insulator : PBT UL94V-0
- Contact : Phosphor Bronze
- Contact Plated : Gold Plated , Tin Plated , Selective Plated
- Shield : Nickel Plated Brass Alloy

MECHANICAL

- Insertion Force : 35Newtons Max
- Extraction Force : 10Newtons Min
- Durability(life test) : 1500 cycles

UNIT : mm

MORLINKOM TECHNOLOGY LTD.

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD
 三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL: Centron@tpts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖	DRAWN BY	日期	DATE
核對	FUFU	2009/01/08	
CHECKED BY	WENDY	比例	SCALE
		1:1	

USB-BR-W/B

圖號 **930-BR/B**
 DRAWING NO.