



## SPECIFICATIONS

### ELECTRICAL

- Contact Current Rating : 1.5 Amperes
- Contact Resistance : 30 mΩ Max
- Insulator Resistance : 1000MΩ Min
- Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds
- Operating Voltage : 150V AC Max

### MATERIAL

- Insulator : PBT UL94V-0
  - Contact : Phosphor Bronze
  - Contact Plated : Gold Plated , Tin Plated , Selective Plated
  - Shield : Nickel Plated Brass Alloy
- ### MECHANICAL
- Insertion Force : 35Newtons Max
  - Extraction Force : 10Newtons Min
  - Durability(Life test) : 1500 cycles

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY

三川精密電子有限公司

TEL:886-2-2686-8788

E-MAIL: Centron@tppts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD

魔林科技有限公司

FAX:886-2-2686-0018

E-MAIL: Cen8888@gmail.com

繪圖

DRAWN BY  
FUFU

日期

2009/04/16

USB-AR-1-W

圖號 930-AR-1-W/B

核對 CHECKED BY

WENDY

比例 SCALE

1:1

USB-AR-1-W

DRAWING NO.

DRAWING NO.